

# 325 Machine

► [www.bianchivending.com](http://www.bianchivending.com)

## USER INTERFACE

- . TACTILE SELECTION PANEL (SOFT TOUCH TECHNOLOGY) WITH 12 PUSH BUTTONS THAT CAN BE CONFIGURED BOTH AS SELECTIONS OR PRE-SELECTIONS.
- . SHOWCASE FOR INTRODUCTION OF FRESH COFFEE BEANS OR FOR BRANDING.
- . END SELECTION ACOUSTIC SIGNAL.
- . 32 DIGIT ALPHANUMERIC DISPLAY.
- . 170 MM HIGH DELIVERY AREA SUITABLE FOR MUG OR JUG AND FOLDAWAY ESPRESSO CUP SUPPORT.



## TECHNOLOGY



LED, LOW VOLTAGE  
LIGHTING



PATENTED  
ESPRESSO GROUP

## PERFORMANCES FOR AN EFFICIENT COFFEE SERVICE.

LEI SA, semi-automatic OCS machine available in espresso coffee from beans and instant coffee versions with 12 push buttons that can be configured as selection or pre-selection.



## LEI SA SPECIFICATIONS

### ELECTRICAL SUPPLY

230 Vac – 50 Hz / 120 Vac – 60 Hz

### INTERNAL ELECTRICAL SUPPLY

All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistances, the pump and the steam ventilator that are at 230 Vac – 50 Hz or 120 Vac – 60 Hz



### POWER SUPPLY

1.80 kW single boiler espresso version  
2.50 kW double boiler espresso version  
2.20 kW instant version

### WATER SUPPLY

Fitting connection = 3/4"

Water pressure = 0.5 – 6.5 bar



#### LEI SA ESPRESSO

1. TEA
2. COFFEE
3. MILK
4. CHOCOLATE

#### LEI SA INSTANT

1. SUGAR
2. COFFEE
3. CHOCOLATE
4. MILK
5. TEA

VERSIONS LEI SA	E3S ESPRESSO SINGLE BOILER *	E3S ESPRESSO DOUBLE BOILER *	I5S INSTANT *
COFFEE BEANS	<b>1</b>	<b>1</b>	-
INSTANT CANISTERS	<b>3</b>	<b>3</b>	<b>5</b>
<b>DIMENSIONS</b>	H 625 mm x W 395 mm x D 580 mm WEIGHT 31,5 kg -- Inches H 25" X W 15 1/2" X D 23" weight 69 lbs		
<b>CABINET</b>	H 900 mm x W 400 mm x D 590 mm		

\* all versions are available with water system supply or with autonomous tank

## FEATURES

- Great flexibility of configuration and a wide choice of versions with water system supply or with autonomous tank.
- Mixers and boiler assembly are extractable to make maintenance operations easier.
- Standard boiler for Espresso: 1500 W – 150 cc. Double boiler available by adding a boiler 700 W – 180 cc. for higher performances (long drinks).
- Boiler for instant: 2000 W - 3,6 litres.
- Liquid waste tray: 1.9 litres with visible signal for maximum water level.
- Coffee waste tray: 60 pods with counter software management.
- Autonomous tank: 3.6 litres of water available placed behind the product canisters and possibility to fill with door closed.

## PRODUCT CAPACITY

	single canister	double canister
Coffee beans	0.80 kg	-
Instant coffee	0.45 kg	-
Powder milk	0.55 kg (1.75 lt)	1.40 kg (3.5 lt)
Whitener	1.20 kg (1.75 lt)	2.90 kg (3.5 lt)
Chocolate	1.30 kg (1.75 lt)	3.00 kg (3.5 lt)
Lemon tea	2.00 kg (1.75 lt)	-
Tea	1.00 kg (1.75 lt)	-
Soup	1.25 kg (1.75 lt)	-
Sugar	1.70 kg	-

## PAYMENT SYSTEM

- compatible with validator or cashless system - parallel protocols, EXE, MDB.

## ACCESSORIES KIT

- Equipped cabinet.
- Free vend panel.
- RS232 module.
- EXE/MDB kit.
- Visual Smart Programmer Speed that allows the upload of the firmware and settings and the download of the settings and audit without a PC.
- Cup stations lighting kit through by software.

## ENVIRONMENT

- Backlighted keyboard with led.
- In compliance with RHOS and WEEE.



**Bianchi Vending Group** • info@bianchivending.com

Corso Africa 9, 24040 Zingonia di Verdellino, Bergamo, Italia tel. +39.035.45.02.111, fax. +39.035.883.304

Specifications and technical information given are indicative and may be subject to change without prior notice. ZD-LEI SA-ED10/2012/EN